

# Offline Contact Cleaner : OCC 400



OCC 400 is a high precision cleaning multi-use spray for metal parts in electrical equipment which prevents electrical and electronic malfunction caused by carbon deposition, water penetration, humidity, rust and corrosion, etc. It has excellent surface wettability due to its low surface tension which provides high penetration into the carbon, resinous materials, oil and grease, grime and marks deposited onto the metal surfaces for their efficient removal.

## Salient Features

- Penetrates, cleans, lubricates and protects metal surfaces from rust and corrosion.
- Displaces moisture, lubricates and prevent corrosion of the equipment surfaces for their smooth functioning.
- High penetrative power enables it to loosen rust-metal bond of various rusted metal parts.
- Eliminates oil and grease, dirt, grime etc. from different surfaces.
- Restores resistance values by reducing current leakage.
- Frees seized rusted parts by penetrating into the finest pores and cracks and helps restore water-damaged electrical equipment.
- Faster evaporation rate helps in quickly drying out electrical systems eliminating moisture enforced short circuits.
- Can be used on all metals and alloys.
- It is safe on plastics, coatings, rubbers and painted surfaces.
- Free of CFC, HCFC and chlorinated solvents.
- Free of heavy metals like Pb, Cr VI, Cd and Hg.

## Application Areas

- Recommended for cleaning and protection of electrical connectors, relays, circuit breakers, motors, transformers, generators, switch gears, electronics, alarm systems, starters, battery terminals, spark plugs, engines, etc.
- Imparts excellent lubrication to moving parts of any equipment or machinery.
- Repairs in hard to reach areas.
- Imparts abrasion resistance to different surfaces.

## Physical and Chemical Data

- |                                      |                              |
|--------------------------------------|------------------------------|
| • Appearance                         | : Clear and clean            |
| • Colour                             | : Water white to pale yellow |
| • Odour                              | : Characteristic             |
| • Density, gm/cc                     | : 0.80 +/-0.025              |
| • Solubility                         | : Insoluble in water         |
| • Flash Point (COC), °C              | : 9                          |
| • Kinematic Viscosity (at 25°C), cSt | : 1.766                      |
| • Dielectric Strength, KV            | : 23.57                      |

## Usage Guidelines

Shake the CAN/Carboy well before each usage. Do excess wetting of the surface to loosen rusted or jammed parts. To remove carbon deposit, grease, oil, hydraulic fluids and related contaminants, spray until clean. Do not use on activated equipment, allow the solvent to evaporate before reactivation. In dipping applications, agitation accelerates the cleaning process. Dip tank should be suitably covered when not in use to avoid undue evaporation. Read all instructions on the CAN/Carboy carefully and follow all precautions and guidelines before use.

## Packaging

Aerosol CAN's of 160 & 280g and Carboys of 05 & 10 lts. Best before 3 years from the date of manufacturing.

## Health and Safety

Observe good chemical hygiene practices. Work practice should minimize contact with skin, eyes, and clothes by wearing safety goggle, mask, gloves etc. Wash hands after handling. Being very highly flammable, avoid smoking or use open fire or other sources of ignition during usage. Provide adequate ventilation and easy access to water supply or an emergency shower. Keep away from extreme heat. Store in a cool, dry and shaded place when not in use.

*Disclaimer: The data, information and suggestion contained in this literature are based on our study and experience. Since the usage conditions and working methods adopted by the buyer's are beyond our control, it is recommended that users satisfy themselves with the actual performance of the product under their respective application conditions. Please refer to Product Label and Material Safety Data Sheet for Health and Safety Information before using the product. Solvclean will not be liable for any loss or damage arising from its product, whether direct, indirect, incidental or consequential, including warranty, contract, negligence or strict liability. This supersedes all previous technical literatures on this product by Solvclean Specialities India LLP.*

---

# Solvclean Specialities India LLP

Regd. Off. : FL-C/1401, M/S B.K.S. Galaxy, Plot 11&15, Sector-35F, Owe Kharghar  
Navi Mumbai – 410 210, Maharashtra (INDIA)

Contact No. : +91 7400293519

Email : solvcleanpecialities@gmail.com